

Ficha técnica :

100 SEC




Capacities		Métrico
Working height	h21	9.93 m
Platform height	h7	7.93 m
Platform capacity	Q	227 kg
Lift capacity - Extension deck		113 kg
Number of people (inside / outside)		2 / 0
Weight and dimensions		
Platform weight*		1959 kg
Platform dimensions (length x width)	lp / ep	2.26 m x 0.80 m
Platform dimensions with extension (length x width)		3.18 m x 0.80 m
Overall width	b1	0.81 m
Overall length	l1	2.44 m
Overall height	h17	2.26 m
Overall length (stowed)	l9	2.44 m
Overall height (stowed)	h18	1.91 m
Overall length with platform extension	l15	3.33 m
Internal turning radius (over tyres)	b13	0 m
External turning radius	Wa3	2.13 m
Ground clearance with pothole guards deployed	m6	0.02 m
Ground clearance at centre of wheelbase	m2	0.09 m
Wheelbase	y	1.85 m
Performances		
Drive speed - stowed		3.50 km/h
Drive speed - raised		0.80 km/h
Raise speed / Lower speed		28 s / 24 s
Gradeability		25 %
Permissible leveling		3 °
Permissible leveling (side)		1.50 °
Wheels		
Tyres type		Tyres Type Non Marking
Dimensions of front wheels / rear wheels		0,38x0,13m - 0,38x0,13m
Drive wheels (front / rear)		2 / 0
Steering wheels (front / rear)		2 / 0
Braking wheels (front / rear)		2 / 2
Engine/Battery		
Electric Pump		3 kW
Battery / Batteries capacity		6 V / 225 Ah
Integrated charger (V / A)		24 V / 20 A
Miscellaneous		
Hydraulic tank capacity		17 l
Sound level at platform		79 dB
Noise to environment (LwA)		< 70 dB
Vibration on hands/arms		< 2.50 m/s ²
Standards compliance		
This machine is in compliance with:		European directives: 2006/42/EC- Machinery (revised EN280:2013) - 2004/108/EC (EMC) - 2006/95/EC (Low voltage)


*Varies according to options and standards of the country to which the machine is delivered

100 SEC - Diagramas de carga

Load Chart metric



100 SEC - Diagrama dimensional



Equipamiento

Estándar
220V predisposition in the platform
Anti-overtuming bar with automatic operation
Anti-slip step
Audible alarm and illuminated indicator lamp (leveling, overload, lowering)
Battery charge indicator lamp
CAN bus technology
Dynamic hydraulic braking on front wheels
Emergency stop button in platform and on frame
Folding rails with half height swing gate
Hom in the platform
Hour meter
Integrated charger
Integrated diagnostic assistance
Manual emergency lowering
Multi-voltage integrated charger
Non-marking rubber tyres
Platform access gate
Pothole protection with automatic operation
Rear wheel multiple disc brakes
Swing out component trays
Opcional
Air predisposition
Beep on every movement
Biodegradable oil
Platform power supply (plug + differential circuit breaker)
Safety harness



Siège Social
430 rue de l'Aubinière - 44150 Ancenis Cedex - France
Tel: +33(0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97
www.manitou.com



Esta publicación describe las versiones y posibilidades de configuración de los productos Manitou que puedan diferir en equipamiento. Los equipamientos presentados en este folleto pueden ser de serie, opcionales o no estar disponibles en algunas versiones. Manitou se reserva el derecho, en cualquier momento y sin previo aviso, de modificar las especificaciones descritas y representadas. Las especificaciones aportadas no comprometen al fabricante. Para más información, póngase en contacto con su concesionario Manitou. Documento no contractual. Presentación de los productos no contractual. Lista de especificaciones no exhaustiva. Los logos y la identidad visual de la empresa son propiedad de Manitou y no pueden ser utilizados sin autorización. Todos los derechos reservados. Las fotos y los esquemas contenidos en este folleto se ofrecen para consulta y a título indicativo solamente.

MANITOU BF SA - Sociedad anónima con Consejo de Administración - Capital social : 39 668 399 euros - 857 802 508 RCS Nantes